AMENDMENTS TO THE CLAIMS:

Claim 1. (Currently amended) A magnetic bearing control device for controlling a magnetic bearing for supporting a rotor in a non-contact manner, said magnetic bearing control device comprising:

a digital processor which controls said magnetic bearing using a magnetic bearing drive signal; and

a counter for accumulating and counting an actual work time of a designated managed component based upon said magnetic bearing drive signal,

wherein said digital processor performs a comparison between the accumulated actual work time of the managed component counted by said counter and a preset maintenance time, and outputs a signal indicating start of maintenance operation of said managed component on the basis of the result of the comparison.

- Claim 2. (Original) The magnetic bearing control device according to claim 1, wherein said digital processor inhibits the activation of said magnetic bearing control device, after the accumulated actual work time of the managed component counted by said counter exceeds a preset limit time.
- Claim 3. (Original) The magnetic bearing control device according to claim 1, wherein said digital processor comprises a function of said counter.
- Claim 4. (Original) The magnetic bearing control device according to claim 2, wherein said digital processor comprises a function of said counter.

09/891,606 DOCKET NO. K06-135818M/TBS

Claim 5. (Original) The magnetic bearing control device according to claim 1 further comprising:

a display portion for displaying a message or an image on the basis of said signal indicating the start of maintenance operation outputted from the digital processor.

Claim 6. (Original) The magnetic bearing control device according to claim 1 further comprising:

a voice output portion for outputting a sound on the basis of said signal indicating the start of maintenance operation outputted from the digital processor.

Claim 7. (Previously presented) The magnetic bearing control device according to claim 1, further comprising:

a data input device which allows a user to set said preset maintenance time.

Claim 8. (Previously presented) The magnetic bearing control device according to claim 2, further comprising:

a data input device which allows a user to set said preset maintenance time and said preset limit time.

Claim 9. (Currently amended) A magnetic bearing controller comprising:

and

a processor that controls a magnetic bearing <u>using a magnetic bearing drive signal;</u>

a counter that accumulates and counts an actual work time of a managed component

09/891,606 DOCKET NO. K06-135818M/TBS

based upon said magnetic bearing drive signal,

wherein said processor further compares the accumulated actual work time with a preset maintenance time.

- Claim 10. (Previously presented) The controller of claim 9, wherein said processor outputs a maintenance signal based upon said comparison.
- Claim 11. (Previously presented) The controller of claim 10, wherein said processor outputs said maintenance signal when said accumulated actual work time is greater than or equal to said preset maintenance time.
- Claim 12. (Previously presented) The controller of claim 9, wherein said processor further compares the accumulated actual work time with a preset limit time.
- Claim 13. (Previously presented) The controller of claim 12, wherein said processor inhibits activation of said magnetic bearing based upon the comparison of said accumulated actual work time with a preset limit time.
- Claim 14. (Previously presented) The controller of claim 13, wherein said processor inhibits activation of said magnetic bearing when the accumulated actual work time is greater than or equal to said preset limit time.
- Claim 15. (Previously presented) The controller of claim 9, further comprising a display

09/891,606 DOCKET NO. K06-135818M/TBS

that is responsive to display a maintenance signal based upon said comparison.

- Claim 16. (Previously presented) The controller of claim 9, further comprising a notification device that is responsive to display a maintenance signal based upon said comparison.
- Claim 17. (Previously presented) The controller of claim 9, further comprising a data input device adapted to receive said preset maintenance time.
- Claim 18. (Currently amended) A method for controlling a magnetic bearing comprising:

controlling said magnetic bearing using a processor that provides a magnetic bearing drive signal;

counting and accumulating an actual work time of <u>said magnetic bearing a managed</u>

component using a counter <u>based upon said magnetic bearing drive signal</u>; and

comparing said actual work time and a preset maintenance time using said processor.

Claim 19. (Previously presented) The method of claim 18, further comprising outputting a maintenance signal based upon said comparison.